

bitstrong biomedical

-86°C ULT Freezer DW-86L388J



Energy saving

VIP(Vacuum Insulation Panel) design with extra insulation cuts down on heat loss to cabinet by 25% and helps reduce energy consumption by more than 20%, power consumption only 8 kWh/day



Slim design

Easily fits through every standard lab door and takes a small footprint



Reliable

Cabinet temperature can reach -86°C with temp uniformity within 5°C

Complementary products



CO₂
Backup
Systems



Chart
Recorder



Stainless
Steel
Racks



Cryo
Boxes

Specifications

DW-86L388J

Technical Data

Type	-86°C ULT Freezer
Cabinet Type	Upright
Climate Class	N
Cooling Type	Direct cooling
Defrost Mode	Manual
Refrigerant	HC
Noise Lever (dB)	50

Performance

Cooling performance(°C)	-86
Temperature Range(°C)	-40~-86

Control

Controller	Microprocessor
Display	LED

Electrical Data

Power Supply(V/Hz)	220-240/50
Power(W)	1000
Electrical Current(A)	8

Functions

High/Low Temperature	Y
Remote Alarm	Y
Hot Condenser	Y
Power Failure	Y
Sensor Error	Y
Low Battery	Y
High Ambient Temp	Y
Door Ajar	Y



Accessories

Caster	Y
Foot	Y
Test Hole	Y/2
Shelves/Inner Doors	3/2
Temperature Recorder	Optional
USB Interface	Y
Rs232/485 Interface	Optional
CO ₂ Backup System	Optional
LN ₂ Backup System	Optional
Racks & Boxes	Optional

Dimensions

Capacity(L/Cu.Ft)	388/13.7	
Net/Gross Weight(approx)	255/286(kg)	562.2/630.5(lbs)
Interior Dimensions(W*D*H)	465*630*1310(mm)	18.3*24.8*51.6(in)
Exterior Dimensions(W*D*H)	812*893*1980(mm)	32.0*35.2*78.0(in)
Packing Dimensions(W*D*H)	875*970*2135(mm)	34.4*38.2*84.1(in)
Container load (20'/40'/40'H)	12/24/24	

Accessories & consumables

DW-86L388J

Consumables

Racks		Part Code		
Model	DCJ-54-A		DCJ-54-B	
Q'ty/Layer		3		
Dimension (W*D*H)	138*565*293(mm) 5.4*22.2*11.5(in)		140*565*293(mm) 5.5*22.2*11.5(in)	
Boxes		Part Code		
Model	T130	HBB-200-PP	HBB-281-PC	HBB-200-C
Material	PP	PP	PC	PC
Dimension (W*D*H)	133*133*53.5(mm) 5.2*5.2*2.1(in)			
Q'ty/Rack		20		
Total Q'ty				
Racks		12		
Boxes		240		
Vials	19440	24000	19440	24000

CO₂ Backup System

Model	HBX-IC
Temperature range	-40°C to -70°C

LN₂ Backup System

Model	HBX-ⅡA
Temperature range	-90°C to -135°C

Chart Recorder

Temperature range	+50°C to -115°C
-------------------	-----------------

Others

Certificate	CE,UL
-------------	-------

お問合せ:

■ 輸入販売元

株式会社ビットストロング 画像営業部 https://www.bitstrong.co.jp/ 〒112-0002 東京都文京区小石川2-25-16 パーソナルハウス2F TEL:03-3868-5605 FAX:03-3868-5616	お問合せはこちらから imaging@bitstrong.co.jp 担当：中村、門（モン） また下記Webフォーム https://www.bitstrong.co.jp/store/contact/
--	--

Complementary products



CO₂
Backup
Systems



Stainless
Steel
Racks





Chart
Recorder



Cryo
Boxes