

bitstrong Biomedical

-40°C Biomedical Freezer DW-40L348



Drawer Structure

Multilayer drawer, easy to store and sort



Six Alarm Functions

High/low temperature, power failure, high ambient temp, sensor error, low battery, remote alarm



Durable Refrigeration

Shelf style evaporator, fast cooling speed

Ergonomic Design



Lockable Design



Intelligent Alarm



High Efficiency and Energy Saving



Foot/Caster Design



Test Hole Design



Hydrocarbon Environmentally Friendly

Specifications

DW-40L348

Technical Data

Type	-40℃ Deep Freezer
Cabinet Type	Upright, double door
Climate Class	4
Cooling Type	Direct cooling
Defrost Mode	Manual
Refrigerant	HC
Noise Level (dB(A))	41

Performance

Cooling performance(℃)	-40
Temperature Range(℃)	-20~-40

Control

Controller	Microprocessor
Display	LED

Electrical Data

Power Supply(V/Hz)	220-240/50
Power(W)	280
Electrical Current(A)	2.9

Dimensions

Capacity(L/Cu.Ft)	348/12.3
Net/Gross Weight(approx)	137/145(kg) 302.0/320.0(lbs)
Interior Dimensions(W*D*H)	535*610*1228(mm) 21.1*24.0*48.3(in)
Exterior Dimensions(W*D*H)	790*845*1860(mm) 31.1*33.3*73.2(in)
Packing Dimensions(W*D*H)	852*927*2044(mm) 33.5*36.5*80.5(in)
Container load (20'/40'/40'H)	14/28/28



Functions

High/Low Temperature	Y
Remote Alarm	Y
Power Failure	Y
Sensor Error	Y
Low Battery	Y
High Ambient Temp	Y

Accessories

Caster	Y
Foot	Y
Test Hole	Y
Drawers	12
USB Interface	Optional
Temperature Recorder	Optional
RS485	Optional

Others

Certificate	CE
-------------	----

発売元

株式会社ビットストロング 画像営業部
<https://www.bitstrong.co.jp/>
東京都文京区小石川2-25-16 パーソナルハウス 2F
TEL:03-3868-5605 FAX:03-3868-5616
担当：中村、藤野
また下記Webフォーム
<https://www.bitstrong.co.jp/contact/>
お問合せはこちらから
imaging@bitstrong.co.jp