

bitstrong Biomedical

-40°C Biomedical Freezer DW-40W100



Three Alarm Functions

High/low temperature, power failure, and sensor error



Adjustable Temperature

Adjustable freezer compartment range: -20 °C ~ -40 °C

Ergonomic Design



Lockable design



Intelligent alarm



Test hole design

Specifications

DW-40W100

Technical Data

Type	-40°C Deep Freezer
Cabinet Type	Chest
Climate Class	4
Cooling Type	Direct cooling
Defrost Mode	Manual
Refrigerant	CFC-Free
Noise Level (dB(A))	≦ 45

Performance

Cooling performance(°C)	-40
Temperature Range(°C)	-20~-40

Control

Controller	Microprocessor
Display	LCD

Electrical Data

Power Supply(V/Hz)	220-240/50	115/60
Power(W)	260	255
Electrical Current(A)	2.5	5.0

Dimensions

Capacity(L/Cu.Ft)	100/3.5
Net/Gross Weight(approx)	43/46(kg) 94.8/101.4(lbs)
Interior Dimensions(W*D*H)	500*385*630(mm) 19.7*15.2*24.8(in)
Exterior Dimensions(W*D*H)	685*650*810(mm) 27.0*25.6*31.9(in)
Packing Dimensions(W*D*H)	740*650*880(mm) 29.1*25.6*34.6(in)
Container load (20'/40'/40'H)	54/108/162



Functions

High/Low Temperature	Y
Power Failure	Y
Sensor Error	Y

Accessories

Test Hole	Y
-----------	---

Others

Certificate	CE
-------------	----

発売元

株式会社ビットストロング 画像営業部
<https://www.bitstrong.co.jp/>
東京都文京区小石川2-25-16 パーソナルハウス 2F
TEL:03-3868-5605 FAX:03-3868-5616
担当：中村、藤野
また下記Webフォーム
<https://www.bitstrong.co.jp/contact/>
お問合せはこちらから
imaging@bitstrong.co.jp