

bitstrong Biomedical

Personal -86°C ULT Freezer



DW-86L100J

Typical Installation and Application

Suitable for clinical, medical, scientific research, quarantine and other departments to store items under low temperature conditions. Applicable for universities, hospitals, disease prevention and control centres, blood stations, scientific research institutes, electronics and chemical enterprise laboratories and biomedical engineering research institutes.

For storage of biological products and biological samples such as red and white blood cells, viruses, bone and bacteria. Also used for electronic devices and other materials used for cryogenic tests.



Energy Efficient, Safe and Reliable

High efficiency HC refrigeration system, optimised for energy efficiency delivering a power consumption figure of just 5.5 kW-h/24 h



Personal ULT Storage

810mm cabinet height makes it easy to place on or under bench, saving storage space. Stackable design.



Ergonomic Design

Ergonomic handle design ensures easy one-hand door opening.



Low Noise

Optimized noise reduction cabinet and system design, emits sound level of only 46.8 dB.

株式会社ビットストロング 画像営業部
<https://www.bitstrong.co.jp/>
 東京都文京区小石川2-25-16 パーソナルハウス 2F
 TEL:03-3868-5605 FAX:03-3868-5616

担当：中村、藤野
 また下記Webフォーム
<https://www.bitstrong.co.jp/contact/>
 お問い合わせはこちらから
imaging@bitstrong.co.jp



bitstrong Biomedical -86°C Personal ULT Freezer

Energy-efficient HC refrigeration design. Secure and reliable. Intelligent Control.

VIP insulation and multilayered sealing design
70mm insulating layer with 25mm VIP and 4 layers of gasket improves energy efficiency and reduces heat loss to ensure superior heating preservation time in event of power failure.

Optional IoT Module
Real time monitoring of cabinet temperature, temperature setting, high and low temperature alarm value, temperature curve, alarm log and event log.

Ergonomic design for easy door opening and closing. Lockable and equipped with 4 keys as standard with the availability of adding a padlock for extra security when required.

Double stainless-steel inner doors to prevent cooling loss when opening the outer door, easy to clean.

Filter is easy to remove and clean without the need for tools.

4 casters + 2-foot locks, easy to move, lock and level.

- User-settable parameters such as temperature pre-set and alarms.
- Real-time cabinet temperature display, alarm information, power supply and compressor start/stop status.
- Standard USB port capable of storing more than 15 years of operating data for compliance.



Microprocessor control system

- Microprocessor control with LED temperature display. The adjustable precision is 1 °C. And the temperature in the unit is adjustable from -40 °C to -86 °C.
- Cabinet temperature/voltage/ambient temperature checking are available.
- Multiple fault alarms: High/low temperature, high/low voltage, high ambient, sensor error, door ajar, power failure, low battery, remote alarm, and hot condenser alarm.
- Two types of alarms: Audible buzzer alarm and flashing light alarm.
- Battery backup alarm function operates continuously for >24hrs in the event of a power outage.
- Standard configuration: RS485 port and USB interface.
- Standard 5V power supply available for test equipment.
- Optional IoT module.



Superior thermal insulation performance

70mm super thick insulation layer design, aviation vacuum insulation material VIP, thickness of 25 mm or more, 4 layers of silicone seal, superior thermal insulation and energy saving effect.



Porthole

Portholes as standard, allows for independent testing of cabinet temperature.



Security lock

Standard door lock and padlock to ensure sample security and prevent unauthorised access.




USB data storage

Capable of storing more than 15 years of data.





Typical Performance Characteristics in 25 °C Ambient: DW-86L100J



Cooling Time(ambient temperature reducing to -80 °C) 310min	Temperature Uniformity ±4°C	Time for inside temperature to rise back from -80 °C to -50 °C naturally at ambient 25 °C 120min
---	---------------------------------------	--

Product Dimension Drawing



KEY

- W0=TOTAL WIDTH
- W1=FREEZER WIDTH
- W2=INNER CABINET WIDTH
- W3=INNER CABINET SHELF WIDTH
- D0=TOTAL DEPTH
- D1=INNER CABINET DEPTH
- D2=INNER CABINET SHELF DEPTH
- H0=TOTAL HEIGHT
- H1=INNER CABINET HEIGHT

CODE MODEL	W0	W1	W2	W3	D0	D1	D2	H0	H1
DW-86L100J	770mm	520mm	330mm	314mm	660mm	481mm	465mm	810mm	630mm



Model	DW-86L100J		
Technical Data	Cabinet Type		Upright
	Climate Class		N
	Cooling Type		Direct cooling
	Defrost Mode		Manual
	Refrigerant		HC
	Noise (dB (A))		46.8
Performance	Cooling Performance (°C)		-86
	Temp Range (°C)		-40~-86
Control	Controller		Microprocessor
	Display		LED
Electrical Data	Power Supply (V/Hz)		220~240/50 120/60
	Power (W)		680 680
	Electrical Current (A)		3 6.5
	Capacity (L/Cu.Ft)		100/3.5
Construction	Net/Gross Weight (approx)	(kg)	108/132
		(lbs)	238/291
	Interior Dimension (W*D*H)	(mm)	330*481*630
		(in)	13*19*25
	Exterior Dimension (W*D*H)	(mm)	770*660*810
		(in)	30*26*32
Packing Dimension (W*D*H)	(mm)	830*710*970	
	(in)	32*28*38.5	
Loading Quantities	Container Load (20'/40'/40'H)		44/88/88
Alarms	Remote Alarm		Y
	High/Low Temperature		Y
	Hot Condenser		Y
	Power Failure		Y
	High/Low Voltage		Y
	Sensor Error		Y
	Low Battery		Y
	High Ambient Temperature		Y
	Door Ajar		Y
Accessories	Caster		Y
	Foot		Y
	Porthole		Y/1
	Shelves/ Inner Doors		1/2
	USB Interface		Y
	5V Power Supply Port		Y
	RS485 Port		Y
Certification	CE/UL		Y/Y

Product appearance and specifications are subject to change without notice