

bitstrong Biomedical

Combined Refrigerator and Freezer

— HYCD-282



Ergonomic Design



Refrigerator & Freezer Combination

Independent control panel display for refrigerator section and freezer section



Alarm Functions

High/low temperature, power failure, sensor error, low battery, high ambient temperature, and remote alarm



Standard Stainless Steel Interior

Both refrigerator and freezer chambers have stainless steel interiors, durable, easy to clean and anti-corrosion



Lockable Design



**Intelligent
Alarm**



**Foot/Caster
Design**



**Porthole
Design**

株式会社ビットストロング 画像営業部

<https://www.bitstrong.co.jp/>

東京都文京区小石川2-25-16 パーソナルハウス 2F

TEL:03-3868-5605 FAX:03-3868-5616

担当：中村、藤野

また下記Webフォーム

<https://www.bitstrong.co.jp/contact/>

お問合せはこちらから

imaging@bitstrong.co.jp

Specifications

Technical Data

Type	Combined Refrigerator and Freezer
Cabinet Type	Upright
Climate Class	N
Cooling Type	Refrigerator: Forced air cooling Freezer: Direct cooling
Defrost Mode	Refrigerator: Auto Freezer: Manual
Refrigerant	CFC-Free
Sound level (dB (A))	43

Performance

Temperature Range (°C)	Refrigerator: 2~8 Freezer: -20~-40
------------------------	---------------------------------------

Control

Controller	Microprocessor
Display	LED

Electrical Data

Power Supply (V/Hz)	220~240/50
Power (W)	400
Electrical Current (A)	2.8

Dimensions

Capacity (L/Cu.Ft)	Refrigerator:185/6.5 Freezer:97/3.4	
Net/Gross Weight (approx)	145/160 (kg)	320.0/352.7 (lbs)
Interior Dimensions (W*D*H)	Refrigerator:605*510*720 (mm) Freezer:515*465*440 (mm)	23.8*20.0*28.3 (in) 20.3*18.3*17.3 (in)
Exterior Dimensions (W*D*H)	736*660*1810 (mm)	29.0*26.0*71.3 (in)
Packing Dimensions (W*D*H)	775*720*1930 (mm)	30.5*28.3*76 (in)
Container load (20'/40'/40'H)	21/45/45	



Functions

High/Low Temperature	Y
Remote Alarm	Y
Power Failure	Y
Sensor Error	Y
Low Battery	Y
High Ambient Temp	Y

Accessories

Caster	Y
Foot	Y
Porthole	Y
Shelves/Drawers	Refrigerator: 3/1 Freezer: 0/2
USB Interface	Y

Others

Certification	CE
---------------	----